



www.tierratech.com



Technical Data

Capacty: 75 litres Internal measures: 700 x 350 x 400 mm. Useful basket measures: 660 x 310 x 290 mm. External measures: 860 x 510 x 900 mm. Weight: 71 kg.

Tel. +34 942 269 543

ELECTRICAL CHARACTERISTICS

- Power Supply: 240V.
- Heating element: 1350 W.

ULTRASONIC CHARACTERISTICS

- Ultrasonic Power: 800W (1600W p-p).
- 1 ultrasonic generator with 800W (1600W p-p) output power.
- Working frequency: 40 KHz sweep system ± 2%.
- 16 high-performance IBL piezo-electric transducers in titanium-steel.

CONTROL PANEL

- General switch.
- DEGAS system to degas the water.
- Ultrasounds timer.
- Temperature selector.
- Power level selector: 50%-100%.

FINISHING AND ACCESSORIES

- Tank built in INOX AISI 316 Stainless steel, 2 mm thick.
- External panel in fingerprint-resistant steel, 1 mm thick.
- Thermo-acustic isolator K-Flex Duct Net, 20 mm thick.
- Integrated handles on the external panel.

• Stainless steel basket with anchorage system for loading, unloading and draining pieces.

- 1" inch draining ball valve.
- Height adjustable silentblock legs.
- Insulated tank cover in Stainless-Steel with pneumatic shock absorber.

WARRANTY AND PRODUCT QUALITY: All equipments supplied by TierraTech®, according to the European legislation on CE marking are supplied with an instruction manual in English. The equipments comply the directives on electromanétic compatibility and electrical safety : Directive 2004/108/EC and Directive 2006/95/EC. The equipments have 3 years warranty against manufacturing defects.

Tierra Tech® Spain Parque empresarial Morero · Nave 27 · 39611 Guarnizo, Cantabria · Spain 543 tierratech@tierratech.com

www.tierratech.com